

Model Type	Input Voltage			Output Voltage *				FEATURES								
	110 – 240 VAC (UNIVERSAL INPUT)	110 – 240 VAC (AUTO-RANGING)	110 – 240 VAC (LINK SELECTABLE)	12 VDC	24 VDC	Auxiliary Output Slot	No. of Auxiliary Slots	Cooling			Connections		Mounting			Serial Communications
								CONVECTION	FAN	VOLT FREE RELAYS	KLIPPONS (as standard)	SCREW TERMINALS (as Standard)	Panel Mount	Din Rail	19" Rack	
45 Watt	◆			◆	◆			◆				◆	◆	◆		
75 Watt	◆			◆	◆	◆	1	◆		◆	◆	◆	◆	◆		
130 Watt			◆	◆	◆	◆	2	◆		◆	◆	◆	◆	◆		
170 Watt			◆	◆	◆			◆		**		◆	◆	◆		
200 Watt		◆		◆	◆	◆	1	◆	◆	◆	◆		◆	◆		◆
200e Watt		◆				◆	1		◆	◆	◆		◆	◆		◆
200m Watt		◆				◆	7		◆	◆	◆		◆	◆		◆
400 Watt		◆		◆	◆	◆	2		◆	◆	◆		◆	◆		◆
560 Watt	◆			◆	◆	◆	1		◆	◆	◆		◆	◆		◆
2400R	◆				◆				◆						◆	◆

\* - Specific Output voltages are available on request.

\*\* - External Relay card is available.